



0~30V/0~10A  
0~60V/0~5A  
0~30V/0~20A  
0~60V/0~10A



## ► Introduction

The TP300W/600W series are linear DC power supplies with 1 channel, 300W/600W output. In constant voltage and current operations, the power supply provides high regulation and low ripple & noise. The output ON/OFF control and coarse/fine control enables safe and easy operation. The TP300W/600W series are widely used in applications of powering operational amplifier, push pull stages, logic circuit and definition systems.

## ► Features

- Constant voltage and constant current operations
- Auto CV and CC switch
- Output ON/OFF control
- Preset function, setting of voltage and current with output open circuit (TP-3020/6010)
- High efficiency, light and compact design
- High power density
- Over load and reverse polarity protections
- Dual-color two digital panel meters

# LINEAR MODE DC POWER SUPPLY

## SINGLE OUTPUT SERIES

### ► Specifications

| Model                             | TP-3010  | TP-6005    | TP-3020                            | TP-6010    |
|-----------------------------------|--|------------|------------------------------------|------------|
| <b>Constant voltage operation</b> |  |            |                                    |            |
| Line regulation                   | ≤0.01%+5mV   | ≤0.01%+5mV | ≤0.01%+10mV                        | ≤0.01%+5mV |
| Load regulation                   | ≤0.02%+5mV   | ≤0.02%+5mV | ≤0.02%+10mV                        | ≤0.02%+5mV |
| Ripple & Noise (5Hz~1MHz)         | ≤3mVrms  |            |                                    |            |
| <b>Constant current operation</b> |  |            |                                    |            |
| Line regulation                   | ≤0.2%+3mA  |            |                                    |            |
| Load regulation                   | ≤0.2%+3mA (I≤3A)<br>≤0.2%+5mA (I>3A)<br>≤0.2%+15mA (I≥10A) |            |                                    |            |
| Ripple & Noise (5Hz~1MHz)         | ≤3mArms (I≤3A)<br>≤10mA rms (I>3A)                         |            |                                    |            |
| <b>Display</b>                    |  |            |                                    |            |
| Accuracy                          | Real voltage and current output: ±(1% reading + 2 digits)  |            |                                    |            |
|                                   | Preset voltage and current: ±(1% reading + 8 digits)       |            |                                    |            |
| <b>General</b>                    |  |            |                                    |            |
| Operating environment             | 0°C~40°C, ≤80%RH   |            |                                    |            |
| Storage environment               | -10°C~70°C, ≤70%RH   |            |                                    |            |
| Power source                      | AC110V/220V±10%, 50/60Hz                                   |            |                                    |            |
| Accessories                       | Power cord x1, Operation manual x1, Test lead x1           |            | Power cord x1, Operation manual x1 |            |

### ► Selection Guide

| Model             | TP-3010       | TP-6005      | TP-3020       | TP-6010      |
|-------------------|---------------|--------------|---------------|--------------|
| Output voltage    | 0~30V         | 0~60V        | 0~30V         | 0~60V        |
| Output current    | 0~10A         | 0~5A         | 0~20A         | 0~10A        |
| Voltmeter         | 3 digits LED  | 3 digits LED | 3 digits LED  | 3 digits LED |
| Ammeter           | 4 digits LED  | 3 digits LED | 3 digits LED  | 4 digits LED |
| Resolution        | 100mV/10mA    | 100mV/10mA   | 100mV/100mA   | 100mV/10mA   |
| Fixed output      |               |              |               |              |
| Preset V&I        |               |              | √             | √            |
| Output ON/OFF     | √             | √            | √             | √            |
| Dimension (WxHxD) | 255x155x370mm |              | 255x155x330mm |              |
| Weight            | 10kg          | 10kg         | 14kg          | 14kg         |